CL - Compact Line

LFB-A, rescue pumper

According to ÖBFV-RL FA 16/12/2001

Basic specification

- Type: Oberaigner 718 CDI 6x6
- Engine output: 135 kW (184 PS) Euro 5
- Gearbox: 6-gear NSG 400 transmission
- Wheelbase: 3,290 + 1,100 mm
- Highlights: double floating suspension of the rear axle, four differential locks, simple tires, 600 mm fording depth

- Cabs:
  - Crew: 1+8 (2/3/4)
  - Driver's cab: original MB cab, separate co-driver seat, storage space between the driver and co-driver
  - Rosenbauer crew cabin fix-mounted into the spacious superstructure
  - Three Rosenbauer COMFORT SCBA fixtures facing backwards
  - Folding table in the crew cabin

- Superstructure:
  - CL lightweight superstructure composed of laser-cut aluminum sheets and robust sandwich plates

Roof:
  - Completely walkable, painted with non-slip coating
  - Access ladder
  - LED roof lighting
  - COMFORT roof chest with lid for equipment storage

- Equipment storage:
  - Rosenbauer superstructure with bar locks
  - Rosenbauer COMFORT lowering device for portable pump
  - Rosenbauer turntable with manual lowering possibility for the generator
  - Variable interior design according to fire service requirements using Rosenbauer rotatable, swing and pullout shelves
  - Stowage block for hydraulic rescue device on an angled COMFORT pullout

- Power supply:
  - Rosenbauer 14 kVA, 230/400V generator
  - 230 V socket including compressed air

- Control system:
  - Rosenbauer central electrical system control panel for: rotating warning lights, horn, flashing lights, ambient lighting, traffic control unit, etc.

CL - Compact Line

LFB-A, rescue pumper

- Warning and other lights:
  - Two flashing light arrays on the roof of the driver's cab
  - One flashing light array at the rear
  - LED flashing lights, integrated into the radiator grill
  - Martin fire service, compressor horn
  - LED ambient lighting integrated into the lateral superstructure rims
  - 4x 1,000 W pneumatic lighting mast, extendable height max. 2,000 mm, individual switching

- Additional equipment:
  - 24 V maneuver searchlight mounted on the mirror frame
  - LED traffic control unit
  - Ball head trailer coupling

Technical Data

L x W x H	6,570 x 2,425 x 2,840 mm
Gross vehicle weight	7,000 kg

Contact

Rosenbauer International AG
Paschinger Straße 90
4060 Leonding, Austria
Tel.: +43 732 6794-0
Fax: +43 732 6794-91

www.rosenbauer.com

Text and illustrations are not binding. The illustrations may show optional extras only available at extra charge.
Rosenbauer retains the right to alter specifications and dimensions given herein without prior notice.

Vers. 1.0
DoR_2010-05-04