

ET Efficient Technology

Municipal fire and rescue truck



Basic specifications

- Type: Volvo FMX 440 4x4
 - › Engine Output: 440 hp D13
 - › Transmission: I-Shift automated 12 speed
 - › Wheelbase: 4,900 mm
- Cab:
 - › Crew: 1+5 (2/0/4)
 - › Volvo original crew cab
 - › Original Volvo steps
 - › 4 Rosenbauer COMFORT breathing apparatus
 - › Safety belts on all seats
- Superstructure:
 - › Rosenbauer aluminum superstructure consisting of a self-supporting, screwed sheetmetal and profile construction
- Equipment compartments:
 - › Low storage compartments equipped with a hinged step and optional with COMFORT revolving shelves for the optimum removal and safe storage of equipment.
- Control system:
 - › Control system over gauges and switches or
 - › Pressure governor
- Extinguishing systems:
 - › Type: NH35 combined normal/high-pressure pump
 - › Output: from 3,500 l/min at 10 bar, 400 l/min at 40 bar
 - › Water tank volume: 4,000 l
 - › Foam tank volume: 400 l
 - › Foam proportioning system: FIXMIX 3 + 6 % external foam suction line
- Pressure outlets:
 - › Four manual pressure outlets in the rear side compartments left and right
- Quick attack unit:
 - › Rear-mounted, high pressure hose reel (25 mm hose, 60 m)
- Water monitor
 - › Rosenbauer RM24M on the roof
- Lighting mast:
 - › Rear mounted pneumatic lighting mast with LED lamps

ET Efficient Technology

Municipal fire and rescue truck



- Electrical systems:
 - › LED flashing blue lights integrated in the rear superstructure
 - › Surrounding area lighting with LED spread beam lights mounted on both side of the roof gallery and on the rear
 - › Electric cable winch warn 54 kN

Dimensions and weight

L x W x H	Max 9,150 x 2,500 x 3,800 mm
Permitted gross weight	18,000 kg



Contact

Rosenbauer International Aktiengesellschaft
Paschinger Straße 90
4060 Leonding, Austria
Tel.: +43 732 6794-0
Fax: +43 732 6794-91

www.rosenbauer.com

 www.facebook.com/rosenbauergroup

Text and photos non-binding. The photos may show optional extras only available at extra charge. The right to make changes in accordance with technical progress is retained.

Vers. 1.0
X2U0182 BSta_2016-002-03