

According to EN 1846 / Chile



Base specification

▪ Chassis:

- › Type: Rosenbauer Commander 3,000 4x2 Euro 5
- › Engine output: 265 kW at 2,100 RPM
- › Transmission: Allison 3,000 EVS
- › Wheelbase: 4,500 mm

▪ Driving compartment:

- › Crew: 1 + 7
- › Original Rosenbauer driving compartment, 70" length and 11" height with Bostrom seats
- › Intercom system at all seating spaces

▪ Vehicle body:

- › Rosenbauer aluminum body made from self-supporting screwed and bonded aluminum sheets and profile construction with aluminum sandwich sheets and robust plastic covers

▪ Equipment compartment:

- › COMFORT stowage and equipment carriers for optimized removal and secure storage of equipment, including rotating platform and rotating compartments between the axles, bracket rotating compartment for small extinguishers

- › Color coding for handles and controls
- › LED compartment lighting

▪ Equipment:

- › Customized equipment

▪ Control system:

- › Rosenbauer LCS 2.0 (Logic Control System) based on CAN-bus technology for: rotating beacons, scene lighting, remote power generator start and monitoring, "engine data," jump-starting, chassis tank indicator, pump, etc.

▪ Extinguishing system:

- › Type: Normal pressure pump NH35 (FPN 10-3000 according to DIN EN 1028) with LCS 2.0 display control and central water axis
- › Water tank content: 4,000 l with automatic level regulation
- › Foam tank 200 l
- › 2-stage LP FIXMIX and HP FIXMIX

▪ Rapid intervention hose reel:

- › 2 x rapid intervention hose reel with 60 m hose

- **Pressure outlets:**
 - › 2 x manual discharge outlets left and right
- **Light mast:**
 - › LED light mast rotating and swiveling
- **Additional equipment:**
 - › Hygiene board
 - › Intercom system at all seats
 - › LED roof lighting
 - › Limber unit for 2 x one-man hose reel
 - › Undervoltage protection
 - › LED traffic warning unit
 - › Scene lighting with 5 LED floodlights each along the roof trim on the left and right
 - › Rosenbauer RM24M water/foam monitor
 - › Manual ladder lowering system
 - › Remote generator start
 - › Roof box with LED lighting
 - › Acrylic rear hatch



Dimensions and weight

L x W x H	8,670 x 2,600 x 3,300 mm
Permissible total weight	17,500 kg



Contact

Rosenbauer International AG
Paschinger Strasse 90
4060 Leonding, Austria
Tel.: +43 732 6794-0
Fax: +43 732 6794-91

www.rosenbauer.com

 www.facebook.com/rosenbauergroup

Text and images non-binding. The images may depict special editions that are only available at an additional charge.
Subject to change due to technical advances.

Vers. 1.0
BSta, 31.03.2015