

AT - Advanced Technology

HLF, Rescue Firefighting Group Vehicle



Plant fire brigade Sindelfingen



Basic specification

- **Chassis:**
 - › Type: MB Antos 1843 L Euro 6 4x2
 - › Engine output: 315 kW (428 hp)
 - › Gear box: Mercedes Power Shift 3
 - › Wheelbase: 4,600 mm
 - › Color coding for handles and controls
 - › LED compartment lighting
- **Cab:**
 - › Crew: 1 + 5
 - › Rosenbauer crew cab integrated into vehicle body with a total of 4 SCBA holders (2 Rosenbauer COMFORT SCBA brackets against direction of travel and 2 in direction of travel)
 - › Crew cab doors glass/glass
 - › Rotating steps
- **Equipment compartment:**
 - › COMFORT stowage and equipment carriers for optimized removal and secure storage of equipment, including rotating platform and rotating compartments between the axles, bracket rotating compartment for small extinguishers
- **Equipment:**
 - › Based on DIN 14530-27
 - › including customer-specific additional equipment
- **Control system:**
 - › Rosenbauer LCS 2.0 (Logic Control System) based on CAN-bus technology for: rotating beacons, horn, front flashlights, scene lighting, remote generator start and monitoring, "engine data," jump-starting, chassis tank indicator, pump, etc.
- **Extinguishing system:**
 - › Type: Normal pressure pump N45 (FPN 10-4000 according to DIN EN 1028) with LCS 2.0 display control and central water axis
 - › Water tank volume: 2,500 l with automatic level regulation
 - › Foam tank 200 l in the EC6
 - › DIGIMATIC 42 pressure proportioning system

AT - Advanced Technology

HLF, Rescue Firefighting Group Vehicle



- **Pressure outlets:**
 - › 1 x manual discharge outlets left and right
 - › 4 x manual discharge outlet at the rear
- **Light mast:**
 - › Rosenbauer FLEXILIGHT 8 x 42 W LED
- **Electrical system:**
 - › Martin fire compressor horn with 4 bells
 - › Rosenbauer cab roof extension with integrated LED modules
 - › 2 LED flashing lights integrated in rear
 - › 2 LED flashing lights in radiator grille
- **Additional equipment:**
 - › LED roof lighting
 - › LED maneuvering lights mounted on mirrors
 - › Low-voltage protection
 - › Scene lighting with 6 LED floodlights each along the roof trim on the left and right
 - › Power windows
 - › Central locking for driver's cab / crew cab
 - › High-end LED crew cab lighting
 - › Reversing camera integrated with image display in the control panel
 - › Wing-mounted access plate in area of rear axle
 - › LED traffic warning device
 - › Independently powered heater in crew cabin
 - › Two helmet mounts in the driver's cab, including LED illumination
 - › Rosenbauer RM24 water monitor



Dimensions and weight:

L x W x H	8,100 x 2,500 x 3,300 mm
Total permissible Total weight	18,000 kg

Contact

Rosenbauer Germany GmbH
Rudolf-Breitscheid-Strasse 7914943 Luckenwalde
Tel.: +49 3371 6905 - 0
Fax: +49 3371 6905 818

www.rosenbauer.com

www.facebook.com/rosenbauergroup