

Compact Line

HLF 10, support fire truck fire-fighting vehicle



according to DIN 14530-26



Base specification

- Chassis:
 - › Type: MAN TGL 12.250 BL
 - › Engine output: 184 kW (250 hp) EURO 5
 - › Wheelbase: 3,900 mm
 - › Towing shackles front and rear
 - › Rockinger trailer coupling TK 226 A
 - › Full height locker in front of and behind the rear axle
 - › 4-part scaling ladder on roof
- Cabin:
 - › Crew: 1 + 8 (2/3/4)
 - › Crew cab: integrated into body
 - › Rosenbauer seat bench boxes with 4 seats in direction of travel and 3 against direction of travel for optimum communication with team leader
 - › 4 SCBAs in crew cab (2 each in direction of travel and against direction of travel)
 - › Safety belts for all seats
 - › Auxiliary heating
- Vehicle body:
 - › Rosenbauer superstructure in lightweight design, body made from aluminum laser-cut parts and aluminum sandwich sheets
 - › Subframe is integrated into floor sandwich: especially low loading heights
 - › High capacity body for maximum flexibility and loading volume
- Equipment compartment:
 - › Rosenbauer electrically operated, oversized shutters
- Loading:
 - › Standard equipment according to DIN 14530-26, Table 1
 - › Additional equipment: wet vacuum, telescoping ladder, scaling ladder connection piece, power drill, stretcher N, thermal imaging camera, gas meter
 - › Rapid action dispensers B-CBC on left and right side
- Extinguishing system:
 - › Rosenbauer (N25) firefighting centrifugal pump FPN 10/2000 according to DIN EN 1028-1 Output: 2,000 l at 10 bar according to EN 14466
 - › Extinguishing water tank: 2,000 l with level regulation
 - › 3 B-discharge outlets and 2 fill lines with shut-off device
 - › 1 C-discharge outlet for fast attack
 - › Rapid intervention system via 2C-hoses in bays on the right side

Compact Line

HLF 10, support fire truck fire-fighting vehicle



- Power supply:
 - › 9 kVA power generator, on the right in full height locker
 - › Inlet: AIRBOX (compressed air + 230 V)
 - › Reversing camera
 - › Navigation system
- Additional equipment:
 - › LED scene lighting 2 units left and right and 2 units on rear
 - › LED crew cab lighting, incl. green light
 - › 2 x flashing LED lights in radiator grille
 - › 2 x LED flashing bars on front of driver's cabin
 - › 2 x LED flashing lights on top rear
 - › Martin horn with 4 bells
 - › Maneuvering searchlights on the exterior mirrors
 - › Traffic warning device on rear (6 x LED flashing lights in yellow)
 - › Pneumatic light tower, 6 x 35 W Xenon floodlights, electrically rotating and swiveling
 - › Tactical operational stickers / design stickers / contour indicators
 - › Vehicle body color RAL 3000 fire red



Dimensions and weight:

L x W x H	7,100 x 2,350 x 3,100 mm
Permissible total weight:	11,990 kg



Contact

Rosenbauer International AG
Paschinger Straße 90
4060 Leonding, Austria
Tel.: +43 732 6794-0
Fax: +43 732 6794-91

www.rosenbauer.com

www.facebook.com/rosenbauergroup

Text and images non-binding. The images may depict special editions that are only available at an additional charge.
Subject to change due to technical advances.

Vers. 1.0
ASus_2013-07-01