

CL - Compact Line KLFA-W, Smallfire truck with water



In accordance with ÖBFV-RL FA 16/12/2001 / Karlstetten - Weyersdorf Volunteer Fire Service



Base specification

- Type: Iveco Daily 65 C 17 (or 70 C 17)
- Engine output: 125 kW (170 hp) Euro 5
- Transmission: 6-speed gearbox
- Wheelbase: 3,750 mm
- Permissible total weight: 6,700 kg (or 7,000 kg)

- Cabin:
 - › Besatzung: 1+5 (3/3)
 - › Crew: 1+5 (3/3)
 - › Driver's cabin: Original Iveco driver's cabin, double passenger seating
 - › Rosenbauer crew cabin integrated in vehicle body
 - › 3 Rosenbauer COMFORT SCBA holders arranged against direction of travel

- Vehicle body:
 - › Rosenbauer CL lightweight construction made from laser-cut aluminum sheet and robust sandwich plates

- Roof:
 - › Completely accessible, painted with anti-slip coating
 - › Access ladder
 - › LED roof lighting
 - › COMFORT roof box with cover for equipment

- Equipment compartment:
 - › Rosenbauer manual vehicle body locks. A contour-shaped roller shutter, giving access to all equipment with a single activation. Additional roller shutter in rear or optional rear flap.
 - › Full height locker in front of and behind the rear axle
 - › Rosenbauer COMFORT lowering device for portable fire pump
 - › Rosenbauer rotating platform for generator
 - › Variable interior design according to fire department requirements (rotating, swiveling and sliding shelves)
 - › Holder block for various required equipment, such as motorized chainsaws, submersible pumps etc.

- Power supply:
 - › Rosenbauer RS 14 generator 14 kVA, 230/400 V
 - › 230 V input socket
 - › NATO 12 V jump-start socket

CL - Compact Line

KLFA-W, Smallfire track with water



- Control system:
 - › Rosenbauer LCS (Logic Control System) screen technology, based on modern CAN-Bus technology
- Warning and lighting equipment:
 - › 2 flashing bars on driver cabin roof
 - › 1 flashing beam on rear
 - › Front LED flashing lights, recessed in radiator grille
 - › FIAMM fire compressor horn
 - › LED surrounding area lighting integrated in the side vehicle body covers
 - › Pneumatic light tower 4 x 1000 W, extension height max. 2,000 mm, individual switching
- Extinguishing system:
 - › Rosenbauer FOX III portable fire pump, extinguishing output 1,500 l/min at 10 bar
 - › Ultra-high pressure pump UHPS over PTO, output 38 l/min at 100 bar
 - › 600 l water tank
 - › Automatic level regulation
 - › Tank-to-tank intake line with three-way ball valve, external supply possible in portable pump without decoupling water tank
 - › Rapid intervention:
 - 3 x B-pressure hose with distributor
 - 3 x C-pressure hose with branch pipe
 - Ultra-high pressure hose reel UHPS with 60 m hose
- Additional equipment:
 - › LED maneuvering searchlights
 - › 100 W loudspeaker system
 - › Traffic control unit
 - › Electric stem winch 4.3 t tractive force, cable length 30 m / 8 mm

Dimensions and weight

L x W x H	6,500 x 2,200 x 2,800 mm
Permissible total weight	6,700 kg



Contact

Rosenbauer International AG
Paschinger Strasse 90
4060 Leonding, Austria
Tel.: +43 732 6794-0
Fax: +43 732 6794-91

www.rosenbauer.com

 www.facebook.com/rosenbauergroup

Text and images non-binding. The images may depict special editions that are only available at an additional charge.
Subject to change due to technical advances.

Vers. 1.0
DoR_2010-12-20