

CL - Compact Line

KLF, small firefighting vehicle



according to EN 1846



Base specification

- **Chassis:**
 - › Type: MB Sprinter 516 CDI Euro 6 4x2
 - › Engine output: 120 kW (163 hp) at 3,800 RPM¹
 - › Wheelbase: 3,665 mm
 - › Power takeoff 40 kW
- **Driving compartment:**
 - › Crew: 1 + 5 (2/2/2)
 - › Crew cab:
 - Rosenbauer seat bench box with 2 seats against the direction of travel for best possible communication with the team leader
 - › Rosenbauer seat frame with two seats in direction of travel and shelving system for equipment next to the seat
 - › 2 SCBA holders in crew cab, arranged against direction of travel and storage tower between the seats
 - › 3-point safety belts for all seats
- **Body type:**
 - › Box-type van with Rosenbauer alloy roller shutters with key; left, right and on rear
 - › Interior made from aluminum profiles and aluminum sandwich technology safety partition wall between crew cabin and equipment compartment
 - › Pivoting doors in the crew cab with central locking
- **Roof:**
 - › Accessible glass-fiber reinforced plastic roof with integrated warning devices and anti-slip coating
 - › Ladder support for hook ladder and multi-purpose ladder
 - › Swivel-mounted hinged ladder
- **Equipment compartment:**
 - › Rosenbauer COMFORT stowage systems.
 - › Holders for secure storage of equipment as well as ergonomic removal
 - › 2 drawers at the rear
- **Payload:**
 - › According to Vienna fire department customer requirement
- **Extinguishing system:**
 - › Water tank 400 l
 - › 1-stage Rosenbauer centrifugal fire pump N10
 - › Performance: 1,000 l at 10 bar
 - › Operation via display
 - › DIGIMATIC 12 foam proportioning system

CL - Compact Line

KLF, small firefighting vehicle



- **Control system:**
 - › Rosenbauer electrical system with display for switching and monitoring the rotating beacons, horn, flashing lights, scene lighting, traffic control unit, pump etc.
- **Power supply:**
 - › 230 V input socket
 - › Battery chargers
 - › NATO 12 V external starting socket
- **Additional equipment:**
 - › Equipment compartment LED lighting light strips
 - › Independently powered heater
 - › Traffic-directing LED device
 - › Power generating set 6.5 kVA (230 V) in engine compartment
 - › Reversing camera
 - › Navigation system
 - › 2 x LED flashing bars on front of glass-fiber reinforced plastic driver's cab
 - › Martin horn



Dimensions and weight

L x W x H	6,200 x 1,995 x 2,860 mm
Permissible total weight	5,300 kg



Contact

Rosenbauer International AG
Paschinger Straße 90
4060 Leonding, Austria
Tel.: +43 732 6794-0
Fax: +43 732 6794-91

www.rosenbauer.com

www.facebook.com/rosenbauergroup

Text and images non-binding. The images may depict special editions that are only available at an additional charge.
Subject to change due to technical advances.

Vers. 1.0
BSta, 21.07.2015