

CL - Compact line Portable pump vehicle - water PPV-W



In accordance with DIN 14530-17 / Landshut volunteer fire department



Base specification

- Type: Iveco Daily 70 C 17
- Engine output: 125 kW (170 hp) Euro 5
- Transmission: Automatic AGILE 6-speed gearbox
- Wheelbase: 3,750 mm
- Permissible total weight 7,200 kg

- Cab:
 - › Crew: 1 + 5 (2/2/2)
 - › Driver's cab: Original Iveco driver's cab, single passenger bench seat
 - › Large Rosenbauer crew cab integrated in vehicle body
 - › 2 Rosenbauer COMFORT SCBA holders arranged against the direction of travel and 2 in direction of travel

- Vehicle body:
 - › Rosenbauer CL lightweight construction made from laser-cut aluminum sheet and robust sandwich plates

- Roof:
 - › Lowering system for 4-part extension ladder

- Equipment compartment:
 - › Rosenbauer electric vehicle locks, a contour-shaped roller shutter on each side, giving access to all equipment with a single activation. Additional roller shutter in rear or optional rear flap
 - › Full height locker in front of and behind the rear axle
 - › COMFORT pull-out platform for portable pump
 - › Variable interior designs according to fire department requirements (rotating, swiveling and sliding shelves)
 - › Holder block for various required equipment, such as motorized chainsaws, submersible pumps etc.
 - › Rosenbauer COMFORT - slide tray for tools and submersible pumps

- Power supply:
 - › BECKER 6.5 kVA built-in generator incl. 4 x 230 V sockets
 - › 230 V input socket
 - › NATO 12 V jump-start socket

CL - Compact line Portable pump vehicle water PPV-W



- Control system:
 - › Rosenbauer LCS (Logic Control System) screen technology, based on modern CAN-Bus technology

- Warning and lighting equipment:
 - › 2 flashing LED bars on driver cab's roof
 - › 1 flashing LED bars in rear
 - › Front LED flashing lights, recessed in radiator grille
 - › Martin fire compressor horn
 - › LED surrounding area lighting integrated in the side vehicle body covers
 - › Pneumatic light mast 4 x 40 W LED, electrically rotating and swiveling, extension height max. 2,000 mm, individual switching

- Extinguishing system:
 - › Rosenbauer FOX III portable pump extinguishing output 1,500 l/min at 10 bar
 - › 800 l water tank
 - › Automatic level regulation
 - › Tank-to-pump intake line with three-way ball valve, external supply possible in TS without decoupling water tank
 - › Rapid intervention: 1 x B pressure hose with distributor
 - › Hose reel with 50 m stable C - rapid intervention hose reel

- Additional equipment:
 - › LED maneuvering searchlights
 - › 100 W loudspeaker system
 - › Traffic control device

Dimensions and weight

L x W x H	6,300 x 2,200 x 2,800 mm
Permissible total weight	7,200 kg



Contact

Rosenbauer International AG
Paschinger Strasse 90
4060 Leonding, Austria
Tel.: +43 732 6794-0
Fax: +43 732 6794-91

www.rosenbauer.com

 www.facebook.com/rosenbauergroup

Text and images non-binding. The images may depict special editions that are only available at an additional charge.
Subject to change due to technical advances.

Vers. 1.0
REhr_2013-06-10