

## National 119 Rescue Headquarters, South Korea



### Basic specification

- **Chassis**
  - › Type: MAN TGS 28.440 6x2-4 BL
  - › Engine output: 324 kW (440 HP) at 1900 RPM, EURO 6
  - › Transmission: ZF 12 AS 2330 OD MAN TipMatic
- **Driving compartment**
  - › Crew: 1 + 1
  - › Driver's cab: original driver's cab
- **Vehicle body**
  - › Rosenbauer aluminum form pipe frame body with cavity coating and aluminum paneling
  - › Roof cover made from aluminum sheet painted red
  - › Profile rails for individually adjustable interior
- **Löschmitteltanks**
  - › Water tank: 3,000 l
  - › Foam compound tank Class A: 100 l
  - › Foam compound tank Class B: 200 l
- **Extinguishing system**
  - › Type: Rosenbauer N25, single stage normal pressure pump
  - › Output: 2,500 l/min at 10 bar
  - › Pump pressure governor
- **Proportioning system**
  - › Type: Rosenbauer DiGIMATIC 42
  - › Normal pressure proportioning system electrically driven and electronically controlled
  - › Output: 36 l/min at 10 bar
  - › Proportioning ratio: 0.1 - 6% stepless
- › Type: Rosenbauer CONTI CAFS 15 C
- › Compressed air foam system
- **Equipment compartment**
  - › Rosenbauer roller shutters with barlocks seal the equipment compartments dust-tight
  - › COMFORT full height lockers and rotating compartments for optimized removal and secure storage of equipment
- **Floodlight towe**
  - › Rosenbauer FLEXILIGHT LED 8 x 42 W
- **Special tanks**
  - › Additive 1: 100 l
  - › Additive 2: 50 l
  - › Sewage tank: 600 l

# HAZMAT DECON TLF 3000/300 CAFS



- **Control system**
  - › Rosenbauer main electrics LCS 2.0
- **Deco unit**
  - › Installed rear side wet area
  - › Awnings in the entry/exit area
  - › Extendable jacks for stabilizing the vehicle during operation
  - › Surface decontamination with spray bar
- **Cleaning technology**
  - › Waterwork
  - › Chemical proportioning system
  - › Cold water high pressure unit
  - › Hot water steam unit
  - › Wastewater system
- **Power generator**
  - › Built-in unit 40 kVA
- **Special equipment**
  - › Extensive equipment for decontamination of persons, surface decontamination, mass decontamination
- **Additional equipment:**
  - › 3 x independently powered heater
  - › Air-conditioner and over pressure unit with carbon filter in the driver's cab
  - › Exhaust system
  - › HP rapid intervention hose reel
  - › Self protection nozzles around the vehicle
- **Trailer**
  - › 2-axle trailer with hydraulic lifting platform rear-side
  - › Equipment: 11 mobile equipment carriers for mass decontamination

## Dimensions and weight:

<b>L x B x H</b>	~ 12,400 x 2,550 x 3,800 mm L: 19,000 mm incl. trailer
<b>Permissible total weight</b>	26.000 kg



## Contact

Rosenbauer International AG  
Paschinger Strasse 90  
4060 Leonding, Austria  
Tel.: +43 732 6794-0  
Fax: +43 732 6794-91

[www.rosenbauer.com](http://www.rosenbauer.com)

 [www.facebook.com/rosenbauergroup](https://www.facebook.com/rosenbauergroup)

Text and images non-binding. The images may depict special editions that are only available at an extra charge.  
Subject to change due to technical advances.

Vers. 1.0  
DaHo 2016-12-21