

AT- Advanced Technology

RLFA 2000, rescue fire truck



According to the Austrian Federal Fire Brigade Association (ÖBFV) / Mondsee Volunteer Fire Department



Basic specification

▪ Chassis:

- › Type: MB Atego 1630 AF 4x4 Euro 6
- › Engine output: 220 kW (300 hp) at 2200 RPM
- › Transmission: 8-speed gearbox PowerShift 3
- › Wheelbase: 3,860 mm

▪ Cab:

- › Crew: 1 + 8
- › Rosenbauer crew cab integrated into vehicle body with a total of 3 Rosenbauer COMFORT SCBA holders
- › Crew cab doors glass/glass
- › Rotating steps

▪ Vehicle body:

- › Rosenbauer aluminum body made from self-supporting screwed and bonded aluminum sheets and profile construction with aluminum sandwich sheets and robust plastic covers

▪ Equipment compartment:

- › COMFORT stowage and equipment carriers for optimal retrieval and secure storage of equipment.
- › Color coding for handles and controls
- › LED compartment lighting

▪ Control system:

- › Rosenbauer LCS 2.0 (Logic Control System) based on CAN-bus technology for: rotating beacons, horn, front flashlights, scene lighting, remote generator start and monitoring, "engine data," jump-starting, chassis tank indicator, pump, etc.

▪ Extinguishing system:

- › Type: Normal pressure pump NH35 (FPN 10-3000 and FPH 40-400 according to DIN EN 1028) with LCS 2.0 display control and central water axis
- › Water tank content: 2000 l with automatic level regulation
- › Foam tank 100 l
- › 3-stage ND FIXMIX
- › Z2 proportioner in compartment 6

▪ Rapid intervention hose reel:

- › HP rapid intervention hose reel equipment compartment 7

▪ Turret:

- › RM24 water/foam monitor

▪ Discharge outlets:

- › 2x manual discharge outlets left and right

AT- Advanced Technology

RLFA 2000, rescue fire truck



- **Light tower:**
 - › FIRECO light tower 8 x LED
- **Electrics:**
 - › Martin fire compressor horn with 4 bells
 - › Rosenbauer cab roof extension with integrated LED modules
 - › 2 LED flashing lights in radiator grille
- **Additional equipment:**
 - › ROTZLER cable winch TR30/6 50kN 2 gear
 - › Independently powered heater in the crew cab
 - › Power generator RS14
 - › Hygiene board
 - › LED roof lighting
 - › Crew cab lighting with LED
 - › LED maneuvering lights mounted on mirrors
 - › Reversing camera with imaging on front display
 - › Wing-mounted access plate in area of rear axle
 - › Low-voltage protection
 - › LED traffic-directing device
 - › Scene lighting with 6 LED floodlights each along the roof trim on the left and right
 - › 2 helmet mounts in the driver's cab
 - › Power windows
 - › Central locking for driver's cab/crew cab
 - › BECKER generator for 220 V
 - › Generator remote start
 - › Roof box with LED lighting
 - › Damped inlet flap
 - › Distance warning device



Dimensions and weight

L x B x H	7,500 x 2,500 x 3,210 mm
Permissible total weight	15,000 kg

Contact

Rosenbauer Österreich GmbH
Paschinger Strasse
4060 Leonding, Austria
Tel.: +43 732 6794-0
Fax: +43 732 6794-84

www.rosenbauer.com

www.facebook.com/rosenbauergroup

Text and images non-binding. The images may depict special editions that are only available at an additional charge.
Subject to change due to technical advances.

Vers. 1.0
Y1U0073 BStA, 11-2016