

Compact Line - Profile (CL-P)

TSF-L, portable pump vehicle - logistics



In accordance with the technical specifications (04/2015) of the Bavarian Ministry of State



Basic specification

▪ Chassis:

- › Type: Iveco Daily 70C18 4x4
- › Engine output: 132 kW at 3,500 RPM EURO 6
- › Wheelbase: 4,100 mm
- › Ball head tow coupling

▪ Cab:

- › Crew: 1 + 5 (2/0/4)
- › Driver's cab: original driver's cab
- › Crew cab: original DOKA

▪ Body type:

- › Rosenbauer aluminum profile-sandwich superstructure
- › Subframe from aluminum
- › Floor plate made of 21 mm aluminum sandwich plate with checker plate top
- › Structural and side walls made of aluminum sandwich panels

▪ Roof:

Not accessible according to DIN 14530 Part 16

Equipment compartment:

- › Rosenbauer body locks with barlock catch in the front area
- › Aluminum lockable storage boxes between the axles
- › Lashing system using airline aluminum rails for roll on/off containers
- › Palfinger loading platform with 1,000 kg lifting capacity, with external manual control, foot control on the platform, and cable remote control inside
- › Variable interior design according to fire department requirements

▪ Payload:

- › Loading techn. construction description of the Ministry of State of Bavaria or in accordance with TSF Standard DIN 14530 Part 16
- › COMFORT inclined extension for portable fire pump
- › COMFORT drawer for digging tools
- › Storage of up to two MECs (1,200 x 800 mm) possible

Compact Line - Profile (CL-P)

TSF-L, portable pump vehicle - logistics



Illumination:

- › Scene lighting using LED technology over the entire structure length
- › Surrounding scene lighting in LED technology over the whole length of the structure, which can also be used as manoeuvring lighting
- › Equipment compartment with circumferential LED lighting

▪ Electronics:

- › Martin fire compressor horn with 4 bells
- › 2 front-integrated LED flashing lights
- › 2 rear-integrated LED flashing lights
- › 2 LED flashing lights in radiator grille
- › Traffic warning device with 2 LED flashing lights
- › Reversing camera system

Dimensions and weight

L x W x H	6,960 x 2,220 x 3,100 mm
Permissible total weight	7,000 kg

Product number PM511



Contact

Rosenbauer Deutschland GmbH
Rudolf-Breitscheid-Strasse 79
14943 Luckenwalde, Germany
Tel.: +49 3371 6905-0
Fax: +49 3371 6905-818

www.rosenbauer.com

www.facebook.com/rosenbauergroup

Text and images non-binding. The images may depict special editions that are only available at an extra charge.
Subject to change due to technical advances

Vers. 1.0
X2V0167 BStA, 03.2017